



SINGLE-SPLIT WALL MOUNTED TYPE

Standard Series

SRK-ZSP-W

NEW



SRK25ZSP-W, SRK35ZSP-W, SRK45ZSP-W



Wireless remote control



SRC25ZSP-W
SRC35ZSP-W



SRC45ZSP-W



SRK-ZSP-W series can be selected for use both R32 and R410A outdoor unit.



Elegant Timeless Design

ZSP series is elegant design fits into any kind of interior decoration.

Energy Class Improvement

All class

Compact and Light weight

The SRK-ZSP-W series offers great installation flexibility.

FUNCTIONS

Energy saving

Air flow

Clean operation & Filter



Comfort & Convenience

Others



SPECIFICATIONS

| Indoor unit | | | | SRK25ZSP-W | SRK35ZSP-W | SRK45ZSP-W |
|-------------------------------------|---------|-------------------------|--|---------------------------|--------------|-------------------------|
| Outdoor unit | | | | SRC25ZSP-W | SRC35ZSP-W | SRC45ZSP-W |
| Power source | | | | 1 Phase, 220 - 240V, 50Hz | | |
| Nominal cooling capacity (Min~Max) | | kW | | 2.5(0.9~3.1) | 3.2(0.9~3.7) | 4.5(1.3~4.8) |
| Nominal heating capacity (Min~Max) | | kW | | 2.8(1.0~4.1) | 3.6(1.0~4.6) | 5.0(1.2~5.8) |
| Power consumption | | Cooling/Heating | | kW | | 0.710 / 0.690 |
| EER/COP | | Cooling/Heating | | | | 3.52/4.05 |
| Max. running current | | A | | 9 | | 14.5 |
| Sound power level | Indoor | Cooling/Heating | | 57 / 57 | | 56 / 62 |
| | Outdoor | Cooling/Heating | | 57 / 56 | | 63 / 64 |
| Sound pressure level | Indoor | Cooling (Hi/Me/Lo) | | 45 / 34 / 23 | | 44 / 39 / 24 |
| | Outdoor | Heating (Hi/Me/Lo) | | 43 / 34 / 26 | | 48 / 41 / 30 |
| Air flow | Indoor | Cooling/Heating | | 47 / 45 | | 51 / 51 |
| | Outdoor | Cooling (Hi/Me/Lo) | | 10.0 / 7.3 / 4.2 | | 9.5 / 6.8 / 4.2 |
| | | Heating (Hi/Me/Lo) | | 9.5 / 7.3 / 5.2 | | 12.0 / 9.2 / 6.2 |
| | | Cooling/Heating | | 23.7 / 19.7 | | 35.6 / 33.4 |
| Exterior dimensions | | HeightxWidthxDensity | | mm | | 267 x 783 x 210 |
| | | | | | | 540 x 645(+57) x 275 |
| | | | | | | 595 x 780(+62) x 290 |
| Net weight | | Indoor / Outdoor | | kg | | 7.0 / 26.5 |
| | | | | | | 7.0 / 28.5 |
| | | | | | | 7.5 / 36.0 |
| Refrigerant | | Type/GWP | | R32 / 675 | | |
| | | Charge | | kg/TCO ₂ Eq | | 0.550 / 0.371 |
| | | | | | | 0.68 / 0.459 |
| | | | | | | 1.10 / 0.743 |
| Refrigerant piping size | | Liquid/Gas | | ø mm | | 6.35(1/4") / 9.52(3/8") |
| Refrigerant line (one way) length | | m | | Max. 15 | | Max. 25 |
| Vertical height differences | | Outdoor is higher/lower | | m | | Max. 10 / Max. 10 |
| Outdoor operating temperature range | | Cooling | | °C | | -15~46 |
| | | Heating | | | | -15~24 |
| Clean filter | | | | | | - |

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.