



SAMSUNG

Samsung 360 Cassette

The Samsung 360 Cassette has an innovative circular design that enables it to match a multitude of interior designs, that adds a touch of style to any room. The Auto Elevation Panel provides quick and comfortable access to dust filters for cleaning. Its minimalistic and elegant styling can help to create a sophisticated and distinctive look in many different sites.

Circular Airflow

Unlike traditional 4-Way Cassette units¹, which create areas of uneven airflow², the 360 Cassette reaches every single corner of a room or space.

Its circular outlet blows cool air in every direction. The bladeless design keeps things comfortably cool without creating a cold draft³, and without blades blocking the airflow it sends 25% more air even further¹.

Airflow Control

The air supply is easily adjusted without the use of flaps. Three booster fans work to alter the direction of airflow from within the cassette's hollow space. A rain-like distribution of the air (known as the 'coanda' effect) keeps the room cool and comfortable at all times. The innovative technology overcomes the usual limits of the conventional outlets that use blades, as they obstruct the air at low angles and cause a significant low airflow⁴. The Motion Detector Sensor (MDS) is available for the 360 Cassette.

Air Purification Panel

The Samsung 360 Cassette offers a Purifying Panel that keeps the indoor air fresh and clean. It is made of a two filter purification system the pre-filter and the PM1.0 Filter and has a superior filter mesh with 0.5mm holes, which is 20% denser than a vinyl chloride type filter. The Pre-Filter captures larger dust particles, stopping them from entering the air conditioning unit. The PM1.0 Filter is not only effective at capturing ultrafine dust of up to 0.3µm in size, but it also sterilizes up to 99% of certain types of bacteria⁵ trapped by the filter using an electrostatic precipitator⁵.

¹Samsung testing compares the 360 Cassette to a conventional 4-Way Cassette type air conditioner.

²The temperature difference is less than 0.6°C within a 9.3m radius.

³No cold draft between 0-1.5m in height (with a 14.0 kW indoor unit) within a 5m radius.

⁴Based on internal testing compared to a general 4-Way Cassette air conditioner.

⁵Verified by Intertek, Report Number RT20E-S0010-R, Issue Date: 17 April 2020. The K-element (Electrostatic Precipitator) of Samsung Electronics can sterilize certain types of bacteria that collected on the filter (Escherichia coli: above 99 %, Staphylococcus aureus: above 99 %).

Samsung 360 Cassette

- 360° air supply.
- Bladeless discharge thanks to three small booster fans.
- Built-in condensation drain pump (750 mm).
- High ceiling mode for heights up to 4.6 m (12.8/14.0 kW), 3.9 m (11.2 kW), 3.5 m (4.5~9.0 kW).
- SPi Ioniser (optional)*.
- Circular or square cassette panel.
- Motion Detector Sensor is optional for square cassette panel.

*Our products have not been tested for their effects on the COVID-19 virus. Therefore, we do not make or give any express or implied claims or guarantees with regard to COVID-19.



Specifications

*3-phase unit available.

Model No.	Indoor Unit			AC071RN4PKG/EU	AC100RN4PKG/EU	AC120RN4PKG/EU	AC140RN4PKG/EU
	Outdoor Unit (1-phase)			AC071RXADKG/EU	AC100RXADKG/EU*	AC120RXADKG/EU*	AC140RXADKG/EU*
Capacity	Cooling		kW	7.10(1.50-8.70)	10.0(3.0-12.00)	12.0(3.5-13.5)	3.50/13.40/15.50
	Heating			8.00(1.90-9.00)	11.2(2.2-15.5)	13.2(3.5-15.5)	3.50/15.50/18.00
UK Capacity	Sensible cooling		kW	4.9	7.4	8.6	9.2
Efficiency	EER		W/W	2.60	3.08	2.69	2.81
	COP ¹			3.23	3.50	3.26	3.35
	SEER ¹		W/W	6.7/	6.8/	6.0/	6.4
	SCOP ¹			4.2/	4.3/	4.0/	4.1
Annual Energy Consumption	Cooling		kWh/a	371	515	700	-
	Heating			1500	1726	2275	-
Sound Pressure	Indoor (H/M/Silent)		dB(A)	36/33/29	44/39/33	45/40/35	45/41/37
	Outdoor (Cooling only)			49	52	54	53
Sound Power	Indoor Unit		dB(A)	53	61	61	61
	Outdoor Unit			65	69	70	69
Airflow Rate	Indoor	Cooling (T/H/M/L)	l/s	291.6/265/238.3	520/425/330	542/425/330	540/452/380
		Heating (T/H/M/L)		291.6/265/238.3	520/425/330	520/425/330	540/452/380
	Outdoor			650	1,200	1,200	1,833
Dimensions (W x H x D)	Indoor		mm	947 x 281 x 947	947 x 365 x 947	947 x 365 x 947	947 x 365 x 947
	Outdoor			880 x 798 x 310	940 x 998 x 330	940 x 998 x 330	940 x 1,210 x 330
Net Weight	Indoor Unit		kg	20.2	23.5	23.5	25.5
	Outdoor Unit			51.0	75.0	81.0	91.5
Refrigerant	Pipe Size Gas		ø, inch	5/8	5/8	5/8	5/8
	Liquid			1/4	3/8	3/8	3/8
	Std/Max Pipe Length (Height)		m	3/50(30)	50(30)	50(30)	75(30)
	Pre Charge to			1.7	2.7	2.7	2.9
	Factory Charging		kg	15	30	30	30
	Additional Charge		g/m	25	50	50	50
	CO ₂ Equivalent (R32 - GWP 675)		tCO ₂ e	1.15	1.82	1.82	1.96
Electrical	Power Supply		V, Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	220-240 V, 50 Hz
	Power Input	Cooling		kW	0.35/2.73/3.60	0.60/3.24/4.70	0.90/4.45/5.30
		Heating	0.35/2.48/3.95		0.46/3.20/5.40	0.75/4.05/5.60	0.70/4.62/7.36
	Current Input	Cooling	A	2.0/11.8/16.0	3.0/14.4/20.4	4.3/19.5/24.0	3.70/20.60/28.00
		Heating		2.0/10.7/17.0	2.5/14.2/23.0	3.7/17.7/26.0	3.7/20.6/28.0
		Interconnecting Communication Cable		mm ²	Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection		

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Accessories						
360 Cassette Fascia Panel - Square WHITE	360 Cassette Fascia Panel - Square BLACK	360 Cassette Fascia Panel - Round WHITE	360 Cassette Fascia Panel - Round BLACK	360 Cassette Fascia Panel Square - PURE Filter	360 Cassette Fascia Panel Square - AutoLIFT	Motion Detect Sensor for PC4NUDMAN/ PC4NUNMAN
PC4NUDMAN	PC4NBDMAN	PC4NUNMAN	PC4NBNMAN	PC6EUCMAN	PC6EUXMAN	MCR-SME
SPi Ioniser	Wireless Remote Controller	Wi-Fi Kit	External Thermostat	Premium Wired Controller	Simple Type Controller	Simplified Wired Controller
MSD-CAN1	AR-KH03E	MIM-H04EN	MRW-TA	MWR-WG00JN/WG00KN	MWR-SH00N	MWR-SH11N