

Samsung Big Ceiling (R

The Samsung Big Ceiling is a simple and stylish indoor unit that delivers a powerful cooling performance. So as well as blending harmoniously into any workplace, it cools a larger area much faster.

Wide & Long distance cooling

Samsung Big Ceiling air conditioner's powerful cooling means you can cool a larger space in a shorter time. It blows cool air over a long distance, up to 15m.

High Elevation (up to 15 m)

It provides much greater flexibility as it can be installed even in places where the elevation is up to a height of 15m – which is higher, or two storeys more, than conventional air conditioners.

WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App¹. Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system² analyses and predicts your needs so it can suggest the best settings for inside your home.

Samsung Big Ceiling (R32)

- Vertical or horizontal installation.
- Air supply by means of one adjustable blade; blade angle between 4° and 45°.
- Long-life washable HD 40 permanent filter is included.







Specifications

*3-phase unit available.

| Model No. | Indoor Unit | | AC100RNCDKG/EU | AC120RNCDKG/EU | AC140RNCDKG/EU | | |
|------------------------------|--|--------------------|--|-------------------|-------------------|--|--|
| | Outdoor Unit (1-phase) | | AC100RXADKG/EU* | AC120RXADKG/EU* | AC140RXADKG/EU* | | |
| Capacity | Cooling | | 10.0(3.0-12.0) | 12.0(3.0-13.5) | 13.4(3.5-15.5) | | |
| | Heating | kW | 11.2(2.2-15.5) | 13.2(3.8-16.5) | 15.5(3.5-18.0) | | |
| JK Capacity | Sensible cooling | kW | 7.13 | 8.17 | 9.01 | | |
| Efficiency | EER | | 3.05 | 2.76 | 2.97 | | |
| | COP ¹ | W/W | 3.44 | 3.44 | 3.41 | | |
| | SEER1 | W/W | 6.1/ A++ | 5.9/ A+ | 6.1/ A++ | | |
| | SCOP1 | | 4.0/ A+ | 4.0/ A+ | 4.0/ A+ | | |
| Annual Energy Consumption | Cooling | 1340- (- | 574 | - | - | | |
| | Heating | kWh/a | 1,820 | - | - | | |
| Sound Pressure | Indoor (H/M/L) | dB(A) | 42/38/34 | 44/41/37 | 46/42/38 | | |
| | Outdoor (Cooling/Heating) | UB(A) | 52/54 | 54/56 | 53/54 | | |
| Sound Power | Indoor Unit | dB(A) | 60 | 62 | 64 | | |
| | Outdoor Unit | UB(A) | 69 | 70 | 69 | | |
| irflow Rate | Indoor Cooling (H/M/L) | l/s | 433/383/317 | 500/400/333 | 567/450/383 | | |
| | Heating (H/M/L) | l/s | 433/383/317 | 533/433/367 | 567/450/383 | | |
| | Outdoor | l/s | 1,200 | 1,200 | 1,833 | | |
| Dimensions (W x H x D) | Indoor | – mm | 1,650 x 235 x 675 | 1,650 x 235 x 675 | 1,650 x 235 x 675 | | |
| | Outdoor | 111111 | 940 x 998 x 330 | 940 x 998 x 330 | 940 x 1,210 x 330 | | |
| let Weight | Indoor Unit | – kg | 42.0 | 41.5 | 41.5 | | |
| | Outdoor Unit | ky | 75.0 | 81.0 | 91.5 | | |
| efrigerant | Pipe Size Gas | ø, inch | 5/8 | 5/8 | 5/8 | | |
| | Liquid | ø, men | 3/8 | 3/8 | 3/8 | | |
| | Std/Max Pipe Length (Height) | — m | 5/50/(30) | 5/50/(30) | 5/75/(30) | | |
| | Pre Charge to | | 30 | 30 | 30 | | |
| | Factory Charging | kg | 2.7 | 2.7 | 2.9 | | |
| | Additional Charge | g/m | 50 | 50 | 50 | | |
| | CO ₂ Equivalent (R32 - GWP 675) | tCO ₂ e | 1.82 | 1.82 | 1.96 | | |
| Electrical | PowerSupply | V, Hz | 220~240 V, 50 Hz | 220~240 V, 50 Hz | 220~240 V, 50 Hz | | |
| | PowerInput Cooling | kW | 0.60/3.28/4.70 | 0.90/4.35/5.30 | 0.80/4.50/6.45 | | |
| | Heating | | 0.46/3.25/5.40 | 0.70/3.83/5.60 | 0.70/4.54/7.36 | | |
| | Current Input Cooling | Α - | 3.0/14.6/20.4 | 5.1/19.1/24.0 | 3.7/19.7/28.0 | | |
| | Heating | | 2.5/14.2/23.0 | 3.9/17.0/26.0 | 3.5/19.8/32.0 | | |
| | MCA | Α | 26.5 | 26.5 | 34.5 | | |
| | MFA | ^ | 30.0 | 30.0 | 40.0 | | |
| | Interconnecting Communiction Cable | mm ² | Screened 0.75-1.5mm², 2 Core, F1 F2 Connection | | | | |

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

| Accessories | | | | | | | |
|-------------|----------------------|---------------------------|------------------|-----------------------------------|--|--|--|
| Wi-Fi Kit | LCD Wired Controller | Remote Temperature Sensor | Touch Controller | External Contact Interface Module | | | |
| MIM-H04EN | MWR-WG00JN | MRW-TA | MWR-SH11N | MIM-B14 | | | |