

Samsung WindFree™ Mini 4-Way Cassette (R32)



The Samsung WindFree™ range keeps you comfortably cool without any cold drafts. It provides intelligent indoor climate comfort thanks to smart controls that adapt to your personal preferences, automatically maintaining optimal conditions.

Wind-Free™ Cooling

WindFree™ technology enhances your indoor comfort by using thousands of micro-holes to disperse fresh air uniformly without any unpleasant blasts of cold wind. In WindFree™ mode, air is spread softly and silently, creating a 'Still Air' environment¹ that provides you total well-being day and night.

Smart Operation

Al Auto Comfort² introduces you to an intelligent way of living. It analyses your room conditions and usage patterns³, and then automatically adjusts the temperature. Temperatures can also be managed remotely using the SmartThings App⁴. Turning it on and off, selecting the cooling mode or scheduling its operation is just one touch away.

WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App⁵. Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system⁶ analyses and predicts your needs so it can suggest the best settings for inside your home.

Samsung WindFree™ Mini 4-Way Cassette

R32)

- 2-Step Cooling: Fast Cooling & WindFree™ Cooling.
- Four-way air supply via independently adjustable blades.
- Blade angle between 32° and 75°; blade width 66 mm.
- Built-in humidity sensor.
- Built-in condensation drain pump (750 mmH2O).









Specifications

	Indoor Unit		AC026RNNDKG/EU	AC035RNNDKG/EU	AC052RNNDKG/EU	AC071RNNDKG/EU		
Model No.	Outdoor Unit (1-phase)		AC026RXADKG/EU	AC035RXADKG/EU	AC052RXADKG/EU	AC071RXADKG/EU		
Capacity	Cooling		2.60(0.87-4.10)	3.50(0.88-4.50)	5.00(1.30-6.20)	6.80(1.50-8.30)		
	Heating	kW	3.40(0.98-4.10)	4.00(1.00-4.80)	5.50(1.30-7.50)	7.50(1.90-9.00)		
K Capacity	Sensible cooling	kW	2.04	2.49	3.49	4.29		
Efficiency	EER		3.88	3.40	3.27	2.47		
	COP ¹	W/W	3.69	3.33	3.62	2.68		
	SEER1		7.1/ A++	7.0/ A++	6.7/ A++	6.1/ A++		
	SCOP ¹	W/W	4.3/ A+	4.3/ A+	4.2/ A+	3.8/ A		
Annual Energy Consumption	Cooling		128	175	261	390		
	Heating	kWh/a	684	684	800	1,474		
Sound Pressure	Indoor (H/M/L)		31/28/25	34/30/25	39/34/29	42/39/36		
	Outdoor (Cooling/Heating)	dB(A)	46/47	48/48	48/48	49/51		
Sound Power	Indoor Unit		48	50	56	58		
	Outdoor Unit	dB(A)	59	61	62	65		
Airflow Rate	Indoor Cooling (H/M/L)	l/s	133.3/116.6/100	153.3/133.3/106.6	175/158.3/141.6	191.6/175/158.3		
	Heating (H/M/L)	l/s	166.6/150/133.3	173.3/150/130	175/158.3/141.6	191.6/175/158.3		
	Outdoor	l/s	500	500	667	850		
Dimensions (W x H x D)	Indoor		575 x 250 x 575	575 x 250 x 575	575 x 250 x 575	575 x 250 x 575		
	Outdoor	mm	790 x 548 x 285	790 x 548 x 285	880 x 638 x 310	880 x 798 x 310		
assette Panel	Model		PC4SUFMAN					
	Dimensions (W x H x D)	mm	620 x 46 x 620					
	Weight	kg	2.7					
Net Weight	Indoor Unit	-	11.5	11.5	12.0	12.0		
	Outdoor Unit	kg	32.5	32.5	43.5	51.0		
Refrigerant	Pipe Size Gas		3/8	3/8	1/2	5/8		
	Liquid	ø, inch	1/4	1/4	1/4	1/4		
	Std/Max Pipe Length (Height)		5/20(15)	5/20(15)	5/30(20)	5/50(35)		
	Pre Charge to	m -	20	20	10	15		
	Factory Charging	kg	0.9	0.9	1.2	1.7		
	Additional Charge	g/m	-	-	15	25		
	CO ₂ Equivalent (R32 - GWP 675)	tCO ₂ e	0.61	0.61	0.81	1.15		
Electrical	Power Supply	V, Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz	220~240 V, 50 Hz		
	PowerInput Cooling	144/	0.16/0.67/1.20	0.18/1.03/1.40	0.31/1.53/2.10	0.35/2.75/3.60		
	Heating	kW	0.20/0.92/1.45	0.19/1.20/1.80	0.35/1.52/2.40	0.35/2.80/3.95		
	Current Input Cooling		1.3/3.5/5.5	1.4/5.0/6.0	2.6/7.0/9.5	2.0/12.0/16.0		
	Heating	A	1.3/4.6/7.0	1.3/5.7/10.5	2.9/7.0/11.0	2.0/12.0/17.0		
	MCA		11.0	11.0	17.5	17.5		
	MFA	A	12.5	12.5	20.6	20.6		
	Interconnecting Communiction Cable	mm²	Screened 0.75-1.5mm², 2 Core, F1 F2 Connection					

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Accessories										
Wireless Remote Controller	Simple Type Controller	Touch Controller	Premium Wired Controller	Panel (Mandatory)	External Thermostat	Wi-Fi Kit	SPi Ioniser			
AR-EH03E	MWR-SH00N	MWR-SH11N	MWR-WG00JN	PC4SUFMAN	MRW-TA	MIM-H04EN	MSD-CAN1			