

SAMSUNG



Samsung WindFree™ 4-Way Cassette R32

The Samsung WindFree™ range keeps you comfortably cool without any cold drafts. It provides intelligent indoor climate comfort thanks to smart controls that adapt to your personal references, automatically maintaining optimal conditions.

WindFree™ Cooling

WindFree™ technology enhances your indoor comfort by using thousands of micro-holes to disperse fresh air uniformly without any unpleasant blasts of cold wind. In WindFree™ mode, air is spread softly and silently, creating a 'Still Air' environment¹ that provides you total well-being day and night.

Smart Operation

AI Auto Comfort² introduces you to an intelligent way of living. It analyses your room conditions and usage patterns³, and then automatically adjusts the temperature. Temperatures can also be managed remotely using the SmartThings App⁴. Turning it on and off, selecting the cooling mode or scheduling its operation is just one touch away.

WiFi Control

Temperatures in your building can be managed remotely using the SmartThings App⁵. Turning it on and off, selecting the cooling mode, scheduling its operation or monitoring the power consumption is just one touch away. The Bixby 2.0 Artificial Intelligence (AI) system⁶ analyses and predicts your needs so it can suggest the best settings for inside your home.

¹ASHRAE (American Society of Heating, Refrigerating, and Air-Conditioning Engineers) defines 'Still Air' as air currents at speeds below 0.15m/s which lacks the presence of cold drafts.

²A Wi-Fi connection and Samsung SmartThings application account are required.

³Stores user data, preferences and usage patterns to suggest the most useful options.

⁴Available on Android and iOS devices. A Wi-Fi connection and Samsung SmartThings application account are required.

⁵Available on Android and iOS devices. A Wi-Fi connection and Samsung SmartThings account are required.

⁶Voice control is supported in English.

Samsung WindFree™ 4-Way Cassette











R32

- 2-Step Cooling: Fast Cooling & WindFree™ Cooling.
- Four-way air supply via independently adjustable blades.
- Blade angle between 34° and 68°; blade width 84 mm.
- Built-in humidity sensor.
- High ceiling mode for heights up to 4.6 m (12.0~14.0 kW), 3.9 m (9.0~10.0 kW), 3.5 m (5.2~7.1 kW).
- Built-in condensation drain pump (750 mmH₂O).



Specifications

*3-phase unit available.

Model No.	Indoor Unit		AC052RN4DKG/EU	AC071RN4DKG/EU	AC100RN4DKG/EU	AC120RN4DKG/EU	AC140RN4DKG/EU	
	Outdoor Unit (1-phase)		AC052RXADKG/EU	AC071RXADKG/EU	AC100RXADKG/EU*	AC120RXADKG/EU*	AC140RXADKG/EU*	
Capacity	Cooling	kW	5.00(1.00-6.50)	7.10(1.50-8.70)	10.0(3.0-12.0)	12.0(3.5-13.5)	13.4(3.5-15.5)	
	Heating		6.00(1.00-7.00)	8.00(1.90-9.00)	11.2(2.2-15.5)	13.2(3.5-15.5)	15.5(3.5-18.0)	
UK Capacity	Sensible cooling	kW	3.89	4.89	7.47	8.41	9.01	
Efficiency	EER	W/W	3.50	2.98	2.92	2.60	2.90	
	COP ¹		4.03	3.27	3.61	3.18	3.16	
	SEER ¹	W/W	7.6/ 	6.7/ 	7.0/ 	6.0/ 	6.6/ 	
	SCOP ¹		4.3/ 	4.2/ 	4.3/ 	4.0/ 	4.3/ 	
Annual Energy Consumption	Cooling	kWh/a	230	371	500	-	-	
	Heating		847	1,500	1,726	-	-	
Sound Pressure	Indoor (H/M/L)	dB(A)	33/31/29	36/33/29	44/39/33	45/40/35	45/41/37	
	Outdoor (Cooling/Heating)		48/48	49/51	52/54	54/56	53/54	
Sound Power	Indoor Unit	dB(A)	49	53	61	61	61	
	Outdoor Unit		62	65	69	70	69	
Airflow Rate	Indoor	Cooling (H/M/L)	l/s	250/233.3/216.6	325 275/241.6	517/417/317	533/433/333	533/450/367
		Heating (H/M/L)		250/233.3/216.6	325 275/241.6	517/417/317	533/433/333	533/450/367
	Outdoor	l/s	667	850	1,200	1,200	1,833	
Dimensions (W x H x D)	Indoor	mm	840 x 204 x 840	840 x 204 x 840	840 x 288 x 840	840 x 288 x 840	840 x 288 x 840	
	Outdoor		880 x 638 x 310	880 x 798 x 310	940 x 998 x 330	940 x 998 x 330	940 x 1,210 x 330	
Cassette Panel	Model	mm	PC4NUFMAN					
	Dimensions (W x H x D)		950 x 48 x 950					
	Weight		6.3					
Net Weight	Indoor Unit	kg	14.5	14.5	18.0	18.0	20.0	
	Outdoor Unit		43.0	51.0	75.0	81.0	91.5	
Refrigerant	Pipe Size	ø, inch	1/2	5/8	5/8	5/8	5/8	
	Gas		1/4	1/4	3/8	3/8	3/8	
	Liquid							
	Std/Max Pipe Length (Height)	m	5/30(20)	5/30(20)	5/50(30)	5/30(20)	5/75(30)	
	Pre Charge to		10	15	30	30	30	
	Factory Charging		1.2	1.7	2.7	2.7	2.9	
	Additional Charge	g/m	15	25	50	50	50	
CO ₂ Equivalent (R32 - GWP 675)	tCO ₂ e		0.81	1.15	1.82	1.82	1.96	
Electrical	Power Supply	V, Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	220-240 V, 50 Hz	
	Power Input		0.33/1.43/2.30	0.35/2.38/3.60	0.60/3.42/4.70	0.90/4.60/5.30	0.80/4.62/6.45	
	Heating	kW	0.25/1.49/2.50	0.35/2.45/3.95	0.46/3.10/5.40	0.75/4.15/5.60	0.70/4.90/7.36	
	Current Input		1.5/6.5/9.5	2.0/10.3/16.0	3.0/15.2/ 20.4	4.3/20.1/24.0	3.7/20.0/ 28.0	
	Heating	A	1.5/6.8/12.0	2.0/10.7/17.0	2.5/13.6/23.0	3.7/18.2/26.0	3.5/21.3/32.0	
	MCA		17.5	17.5	25.0	25.0	33.0	
	MFA	A	20.6	20.6	30.0	30.0	40.00	
Interconnecting Communication Cable		mm ²	Screened 0.75-1.5mm ² , 2 Core, F1 F2 Connection					

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Accessories						
Wireless Remote Controller	Touch Controller	Premium Wired Controller	Panel (Mandatory)	Motion Detect Sensor (950 x 950 panel)	Wi-Fi Kit	SPI Ioniser
AR-EH03E	MWR-SH11N	MWR-WG00JN	PC4NUFMAN	MCR-SMC	MIM-H04EN	MSD-CAN1

Copyright © 2020 Samsung Electronics Air Conditioner Europe B.V. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice and may include preliminary information. Non-metric weights and measurements are approximate. All data was deemed correct at the time of creation. Samsung is not liable for errors or omissions. Some images may be digitally altered. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognised and acknowledged.

Samsung Electronics Air Conditioner Europe B.V.

Evert van de Beekstraat 310, 1118 CX Schiphol
P.O. Box 75810, 1118 ZZ Schiphol
The Netherlands
+31 (0)8 81 41 61 00