

HM_UT 4-WAY SMART CASSETTE



Dedicated for commercial application, the Toshiba Smart Cassette is the perfect mix between comfort, elegance and efficiency.

Efficiency

- Top class SEER and SCOP, thanks to long slit heat exchanger with magic coil treatment, high efficiency fan motor and large opening air conditioning ventilation.
- Energy saving with the occupancy sensor which will automatically switch off the unit if nobody is in the room (TCB-SIR41U-E needed).

Comfort

- Unique flap design for optimal air distribution.
- Individual setting of louver position: 3 different swing modes: standard, diagonally, opposite or turn around.
- 5 fan steps to precisely control the air flow.

Design

- Simple & elegant design fits various rooms.



SCOP MAX



5.51

CAPACITY



5kW > 14kW

OPERATION



-27°C > +52°C

Louver position automatically adjusts to prevent cold draught being felt by users



INDOOR UNITS

RAV-HM561UT-E/TR
RAV-HM801UT-E/TR
RAV-HM1101UT-E/TR
RAV-HM1401UT-E/TR



OUTDOOR UNITS

RAV-GP561ATW-E/TR RAV-GP801ATW-E/TR RAV-GP1101AT-E1/TR1
RAV-GP1401AT-E/TR



REMOTE CONTROLS

RBC-AX41U-E/TR RBC-AXU31-E/TR RBC-AMSU51E-ES(EN)
RBC-AMTU31-E
RBC-ASCU11-E

4-WAY SMART CASSETTE

4-WAY SMART CASSETTE Performance data with Super Digital Inverter Series 1

Outdoor unit		RAV-GP561ATW-E/TR		RAV-GP801ATW-E/TR		RAV-GP1101AT-E/TR		RAV-GP1401AT-E1/TR1	
Indoor unit (Cassette)		RAV-HM561UT-E/TR		RAV-HM801UT-E/TR		RAV-HM1101UT-E/TR		RAV-HM1401UT-E/TR	
Cooling capacity	kW	5.0		7.1		10.0		12.5	
Cooling range (min. - max.)	kW	1.2 - 5.6		1.9 - 8.0		3.1 - 12.0		3.1 - 14.0	
Power input (min. - rated - max.)	kW	C	0.19 - 1.2 - 2.03	0.26 - 1.37 - 2.94		0.56 - 1.90 - 2.80		0.56 - 2.91 - 3.40	
EER		4.17		5.18		5.26		4.30	
SEER		8.17		9.40		9.25		8.87	
Energy efficiency class		C	A++	A+++		A+++		-	
Seasonal electricity consumption	kWh/a	C	214	256		378		845	
Heating capacity	kW	5.6		8.0		11.2		14.0	
Heating range (min. - max.)	kW	0.9 - 8.1		1.3 - 11.3		2.6 - 13.0		2.6 - 16.5	
Power input (min. - rated - max.)	kW	H	0.16 - 1.29 - 2.75	0.20 - 1.45 - 3.15		0.41 - 2.18 - 2.98		0.41 - 3.04 - 4.18	
COP	W/W	4.34		5.52		5.14		4.61	
SCOP		5.01		5.54		5.03		5.00	
Energy efficiency class		H	A++	A+++		A++		-	
Seasonal electricity consumption	kWh/a	H	1058	1287		2556		2685	

4-WAY SMART CASSETTE Physical data indoor

Indoor unit		RAV-HM561UT-E/TR		RAV-HM801UT-E/TR		RAV-HM1101UT-E/TR		RAV-HM1401UT-E/TR	
Air flow (H/L)	m³/h - l/s	1050/750 - 291/208		1920/810 - 533/225		2250/1050 - 625/291		2250/1170 - 625/325	
Sound pressure level (H-M-L)	dB(A)	32-29-26		42-35-27		48-40-31		48-41-33	
Sound power level (H-M-L)	dB(A)	48-45-43		56-49-43		61-54-46		61-55-48	
Dimensions (HxWxD)	mm	256 × 840 × 840		319 × 840 × 840		319 × 840 × 840		319 × 840 × 840	
Weight	kg	20		25		25		25	
Panel dimensions (HxWxD)	mm	30×950×950		30×950×950		30×950×950		30×950×950	
Panel weight	kg	5		5		5		5	

C: cooling mode
H: heating mode