



SINGLE-SPLIT WALL MOUNTED TYPE

Standard Series

SRK-ZSP-W

NEW



SRK25ZSP-W, SRK35ZSP-W, SRK45ZSP-W



Wireless remote control



SRC25ZSP-W
SRC35ZSP-W



SRC45ZSP-W



SRK-ZSP-W series can be selected for use both R32 and R410A outdoor unit.



Elegant Timeless Design

ZSP series is elegant design fits into any kind of interior decoration.

Energy Class Improvement

All class

Compact and Light weight

The SRK-ZSP-W series offers great installation flexibility.

FUNCTIONS

Energy saving

Air flow

Clean operation & Filter



Comfort & Convenience

Others



SPECIFICATIONS

Indoor unit				SRK25ZSP-W	SRK35ZSP-W	SRK45ZSP-W	
Outdoor unit				SRC25ZSP-W	SRC35ZSP-W	SRC45ZSP-W	
Power source				1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min~Max)			kW	2.5(0.9~3.1)	3.2(0.9~3.7)	4.5(1.3~4.8)	
Nominal heating capacity (Min~Max)			kW	2.8(1.0~4.1)	3.6(1.0~4.6)	5.0(1.2~5.8)	
Power consumption		Cooling/Heating	kW	0.710 / 0.690	0.910 / 0.930	1.350 / 1.360	
EER/COP		Cooling/Heating		3.52/4.05	3.52 / 3.87	3.33 / 3.68	
Max. running current			A	9	9	14.5	
Sound power level	Indoor	Cooling/Heating	dB(A)	57 / 57	58 / 58	56 / 62	
	Outdoor	Cooling/Heating		57 / 56	59 / 60	63 / 64	
Sound pressure level	Indoor	Cooling (Hi/Me/Lo)		45 / 34 / 23	45 / 36 / 23	44 / 39 / 24	
		Heating (Hi/Me/Lo)		43 / 34 / 26	44 / 36 / 28	48 / 41 / 30	
Air flow		Cooling/Heating		47 / 45	48 / 48	51 / 51	
	Indoor	Cooling (Hi/Me/Lo)	m³/min	10.0 / 7.3 / 4.2	9.5 / 6.8 / 4.2	9.0 / 7.2 / 3.8	
		Heating (Hi/Me/Lo)		9.5 / 7.3 / 5.2	9.6 / 7.4 / 5.5	12.0 / 9.2 / 6.2	
	Outdoor	Cooling/Heating		23.7 / 19.7	22.8 / 22.0	35.6 / 33.4	
Exterior dimensions		Indoor Outdoor		HeightxWidthxDepth	mm	267 x 783 x 210	
Net weight			Indoor / Outdoor			kg	7.0 / 26.5
Refrigerant		Type/GWP	kg/TCO₂Eq	0.550 / 0.371	R32 / 675		
Refrigerant piping size		Liquid/Gas			ø mm	6.35(1/4") / 9.52(3/8")	
Refrigerant line (one way) length			m	Max. 15			
Vertical height differences		Outdoor is higher/lower	m	Max. 10 / Max. 10			
Outdoor operating temperature range		Cooling Heating	°C	-15~46 -15~24			
Clean filter					—		

* The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.

* Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.

* 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.