



## FNA-A9 / RZAG-A

### Designed to be concealed in walls

- › Combination with new Mini Sky Air to achieve up to 50m total pipe run
- › Ideal for installation in offices, hotels and residential applications
- › Blends unobtrusively with any interior décor: only the suction and discharge grills are visible
- › Its low height (620mm) enables the unit to fit perfectly beneath a window
- › Requires very little installation space as the depth is only 200mm
- › High ESP allows flexible installation

**R-32** BLUEEVOLUTION



FNA-A9



RZAG35A



BRC1H519W



BRC4C65  
(optional)



BRP069A81  
(optional)



WI-FI ADAPTOR

AVAILABLE AS AN OPTION

## FNA-A9 / RZAG-A

**R-32** BLUEEVOLUTION

| Indoor Units                                |                     |                     | FNA35A9     | FNA50A9     | FNA60A9     |
|---------------------------------------------|---------------------|---------------------|-------------|-------------|-------------|
| Capacity                                    | UK Total Cooling    | kW                  | 3.32        | 4.89        | 5.86        |
|                                             | UK Sensible Cooling | kW                  | 2.26        | 3.66        | 4.11        |
|                                             | Nominal Cooling     | kW                  | 3.4         | 5.0         | 6.0         |
|                                             | Nominal Heating     | kW                  | 4.0         | 5.8         | 7.0         |
| Seasonal Efficiency<br>(EN14825)<br>COOLING | Energy Label        |                     | A+          | A+          | A+          |
|                                             | Pdesign             | kW                  | 3.4         | 5.0         | 6.0         |
|                                             | SEER                |                     | 5.90        | 5.90        | 5.70        |
| Seasonal Efficiency<br>(EN14825)<br>HEATING | Energy Label        |                     | A           | A           | A           |
|                                             | Pdesign             | kW                  | 2.9         | 4.0         | 4.6         |
|                                             | SCOP                |                     | 3.90        | 3.90        | 3.90        |
| Nominal Efficiency                          | EER/COP             |                     | 3.90 / 3.50 | 3.80 / 3.40 | 3.40 / 3.30 |
| Air Flow Rate (Cooling)                     | High / Low          | m <sup>3</sup> /sec | 0.145/0.122 | 0.267/0.225 | 0.225/0.025 |
| External Static Pressure                    | High / Nom          | Pa                  | 48/30       | 49/40       | 49/40       |
| Dimensions                                  | Height              | mm                  | 620         | 620         | 620         |
|                                             | Width               | mm                  | 750         | 1150        | 1150        |
|                                             | Depth               | mm                  | 200         | 200         | 200         |
| Weight                                      |                     | kg                  | 23          | 30          | 30          |
| Sound Pressure (Cooling)                    | High / Low          | dBA                 | 33/28       | 36/30       | 36/30       |
| Sound Pressure (Heating)                    | High / Low          | dBA                 | 33/28       | 36/30       | 36/30       |
| Sound Power (Cooling)                       |                     | dBA                 | 53          | 56          | 56          |

| Outdoor Units             |                             |                     | RZAG35A               | RZAG50A                | RZAG60A                |
|---------------------------|-----------------------------|---------------------|-----------------------|------------------------|------------------------|
| Dimensions                | Height x Width x Depth      | mm                  | 820 x 1050 x 480      | 820 x 1050 x 480       | 820 x 1050 x 480       |
| Weight                    |                             | kg                  | 52                    | 52                     | 52                     |
| Electrical Details        | Power Supply                |                     | 1ph                   | 1ph                    | 1ph                    |
|                           | Maximum Input Current (MCA) | A                   | 14.73                 | 14.73                  | 16.70                  |
|                           | Max Fuse Size               | A                   | 16                    | 16                     | 20                     |
|                           | Core / Cable Size           |                     | 3+E / 1.5             | 3+E / 1.5              | 3+E / 1.5              |
| Piping Connections        | Liquid / Gas                | inches (mm)         | 1/4 (6.4) / 3/8 (9.5) | 1/4 (6.4) / 1/2 (12.7) | 1/4 (6.4) / 1/2 (12.7) |
| Pipework                  | Maximum Length              | m                   | 50                    | 50                     | 50                     |
|                           | Maximum Vertical Rise       | m                   | 30                    | 30                     | 30                     |
|                           | Precharged to               | m                   | 30                    | 30                     | 30                     |
|                           | Additional charge           | g/m                 | 20                    | 20                     | 20                     |
|                           | Holding charge              | kg                  | 1.55                  | 1.55                   | 1.55                   |
| Sound Pressure (Cooling)  | Nominal                     | dBA                 | 48                    | 49                     | 50                     |
| Sound Pressure (Heating)  | Nominal                     | dBA                 | 48                    | 49                     | 50                     |
| Sound Power (Cooling)     |                             | dBA                 | 62                    | 63                     | 64                     |
| Operating Range (Cooling) | Min / Max                   | °CDB                | -20 / +52             | -20 / +52              | -20 / +52              |
| Operating Range (Heating) | Min / Max                   | °CWB                | -20 / +24             | -20 / +24              | -20 / +24              |
| Air Flow Rate (Cooling)   | Nominal                     | m <sup>3</sup> /sec | 0.918                 | 0.918                  | 0.918                  |

| Accessory Ref | Description                                                     |
|---------------|-----------------------------------------------------------------|
| BRC1E53A      | Premium wired remote controller (Included as standard)          |
| BRP069A81     | Wifi adaptor for connection to on-line controller               |
| BRC1H519W     | New - wired touch screen remote controller - White              |
| BRC1H519S     | New - wired touch screen remote controller - Silver             |
| BRC1H519K     | New - wired touch screen remote controller - Black              |
| BRC2E52C      | Wired simplified remote controller (without auto swing)         |
| BRC4C65       | Wireless remote controller                                      |
| K.CGM         | Condensing unit guard size 42-71                                |
| K.CGS         | Condensing unit guard size 20-35                                |
| K.CWB90-2     | Condensing unit bracket - up to size 71, max weight 90kg of ODU |
| K.DT1         | Condensate drip tray for use with K.CWB90-2                     |

| Accessory Ref      | Description                                                                                      |
|--------------------|--------------------------------------------------------------------------------------------------|
| K.RSS              | Wireless room mounted temperature sensor and receiver                                            |
| KLIC-DI            | KNX Interface for Sky Air and VRV systems                                                        |
| KRCS01-4           | Remote room mounted temperature sensor                                                           |
| KRP4A53 and UK.FB2 | Unit/group adaptor PCB for remote on/off, status indication and temperature setting              |
| RS-SE              | Service and configuration tool for K.RSS                                                         |
| RTD-10 and UK.FB2  | Enhanced function PCB for Sky Air and VRV, Duty rotation, Lead Lag control and heating interlock |
| RTD-20 and UK.FB2  | Energy control PCB for Sky Air and VRV                                                           |
| RTD-NET and UK.FB2 | Modbus interface PCB for Sky Air and VRV                                                         |

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)