

SLIM DUCTED: RAS - M16U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):



UK



ROI



Hi - Res Image 

CODE			45
Performance			
Indoor Unit		RAS-	M16U2DVG-E
Capacity Code			16
Nominal	Cooling Capacity	kW	4.5
	Heating Capacity	kW	5.5
UK	Cooling Total/Sensible	kW	4.49/3.36
	Heating	kW	3.33
Cooling EN14825	Range Min. - Max.	kW	2.13 - 4.50
	Power Input	kW	0.062
Heating EN14825	Range Min. - Max.	kW	2.33 - 5.50
	Power Input	kW	0.062
Indoor Data			
Air Flow	High - Low	l/s	217 - 117
	High - Low	m3/h	780 - 420
External Static Pressure	Standard (Upper - Lower)	Pa	10 (10 - 45)
Sound Pressure	High - Low	dB(A)	35 - 25
	High - Low (under inlet)	dB(A)	44 - 27
Sound Power	High - Low	dB(A)	50 - 40
	High - Low (under inlet)	dB(A)	59 - 42
Unit	Height x Width x Depth	mm	210 x 900 x 450
	Weight	kg	19
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Remote Controller			WH-TA04NE

Accessories

RB-RWS21-E	Wired Remote Controller
------------	-------------------------

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

