

SLIM DUCTED: RAS - M24U2DVG-E

- Slim design with only 210mm height.
- External static pressure from 10 to 45 Pa.
- Compatible with latest R32 Multi System.
- Inbuilt Condensate drain pump with lift up to 350mm.
- Compliant with European Ecodesign regulation - Lot10.



Retail Price (interactive icons):



UK



ROI



Hi - Res Image 

CODE			71
Performance			
Indoor Unit		RAS-	M24U2DVG-E
Capacity Code			24
Nominal	Cooling Capacity	kW	7.1
	Heating Capacity	kW	8.1
UK	Cooling Total/Sensible	kW	6.84/4.71
	Heating	kW	5.27
Cooling EN14825	Range Min. - Max.	kW	3.28 - 7.10
	Power Input	kW	0.076
Heating EN14825	Range Min. - Max.	kW	3.36 - 8.10
	Power Input	kW	0.076
Indoor Data			
Air Flow	High - Low	l/s	294 - 211
	High - Low	m3/h	1060 - 760
External Static Pressure	Standard (Upper - Lower)	Pa	10 (10 - 45)
Sound Pressure	High - Low	dB(A)	39 - 33
	High - Low (under inlet)	dB(A)	46 - 38
Sound Power	High - Low	dB(A)	54 - 48
	High - Low (under inlet)	dB(A)	61 - 53
Unit	Height x Width x Depth	mm	210 x 1100 x 450
	Weight	kg	22
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	32/25
Remote Controller			WH-TA04NE

Accessories

RB-RWS21-E	Wired Remote Controller
------------	-------------------------

*All [Accessories / Controls](#)

Related Items:

- [BIM Files](#)
- [CAD Files](#)
- [Full Specification](#)
- [Dimensional Drawing](#)
- [Wiring Diagram](#)
- [Airflow/ Fan Curve](#)
- [Noise Curve Data](#)
- [Installation Manual](#)
- [Owners Manual](#)

