

Model name				ARXG18KSLAP	
Power supply				1Ø 230 V ~ 50 Hz	
Available voltage range				198—264 V	
Capacity			kW class	5.0	
Input power	Fan	HIGH		W	63
		MED			38
		LOW			22
		QUIET			19
Running current			A	0.49	
Fan	Airflow rate	Cooling	HIGH	m³/h	940
			MED		750
			LOW		540
			QUIET		480
		Heating	HIGH		940
			MED		750
			LOW		540
			QUIET		480
	Type × Q'ty			Sirocco fan × 3	
	Motor output		W	80	
Recommended static pressure			Pa	0 to 50	
Sound pressure level *	Cooling	HIGH	dB (A)	33	
		MED		29	
		LOW		26	
		QUIET		23	
	Heating	HIGH		33	
		MED		29	
		LOW		26	
		QUIET		23	
Sound power level		Cooling	dB (A)	58	
Heating		59			
Heat exchanger type	Dimensions (H × W × D)		mm	336 × 690 × 26.6	
	Fin pitch			1.30	
	Rows × Stages			2 × 16	
	Pipe type			Copper tube	
	Fin type			Aluminum	
Enclosure		Material		Steel sheet	
Color				—	
Dimensions (H × W × D)	Net		mm	198 × 900 × 450	
	Gross			250 × 1,130 × 580	
Weight	Net		kg	18.5	
	Gross			23.0	
Connection pipe	Size	Liquid	mm (in)	Ø6.35 (Ø1/4)	
		Gas		Ø12.7 (Ø1/2)	
	Method			Flare	
Drain hose	Material			PVC	
	Tip diameter		mm	Ø25 (I.D.), Ø32 (O.D.)	
Operation range	Cooling		°C	18 to 32	
	Heating		%RH	80 or less	
			°C	16 to 30	

NOTES:

- Values mentioned in the table are based on the following conditions:
 - Static pressure: 15 Pa
- The protective function might work when using it outside the operation range.
- *: Sound pressure level:
 - These are the measured values in the manufacturer's anechoic chamber.
 - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.