

1. Specifications

1-1. Indoor units

Type				Wall mounted				
				Inverter, Heat pump				
Model name				ASEG07KETF ASEG07KETF-B	ASEG09KETF ASEG09KETF-B	ASEG12KETF ASEG12KETF-B	ASEG14KETF ASEG14KETF-B	
Power supply				230 V~ 50 Hz				
Power supply intake				Outdoor unit				
Available voltage range				198—264 V				
Capacity	Cooling	Rated	kW	2.0	2.5	3.4	4.2	
			Btu/h	6,800	8,500	11,600	14,300	
		Min.—Max.	kW	0.9—3.0	0.9—3.2	0.9—3.9	0.9—4.4	
			Btu/h	3,100—10,200	3,100—10,900	3,100—13,300	3,100—15,000	
	Heating	Rated	kW	2.5	2.8	4.0	5.4	
			Btu/h	8,500	9,500	13,600	18,400	
		Min.—Max.	kW	0.9—3.4	0.9—4.0	0.9—5.3	0.9—6.0	
			Btu/h	3,100—11,600	3,100—13,600	3,100—18,000	3,100—20,500	
Input power	Cooling	Rated	kW	0.450	0.630	0.935	1.220	
				Min.—Max.	0.25—1.17	0.25—1.21	0.25—1.27	0.25—1.40
	Heating	Rated		0.555	0.620	0.960	1.410	
				Min.—Max.	0.25—1.21	0.25—1.26	0.25—1.52	0.25—1.73
	Fan	HIGH	W	22.1	26.5		33.6	
				15.1	16.0		20.0	
				10.0		11.8		
				6.4		7.1		
Current	Cooling	Rated	A	2.6	3.4	4.8	5.8	
	Heating			3.0	3.4	5.1	6.8	
Energy efficiency class		Cooling		A++				
		Heating (Average)		A+				
Pdesign	Cooling		kW	2.0	2.5	3.4	4.2	
	Heating (Average)			2.3	2.4	2.5	4.0	
SEER	Cooling		kWh/kWh	7.4		7.3	6.9	
SCOP	Heating (Average)			4.1		4.4	4.1	
Annual energy consumption	QCE		kWh/a	95	118	163	213	
	QHE (Average)			785	819	795	1,366	
EER	Cooling		kW/kW	4.43	3.97	3.65	3.44	
COP	Heating			4.52		4.17	3.83	
Sensible capacity	Cooling		kW	1.2	1.6	2.2	3.2	
Power factor	Cooling		%	75	81	88		
	Heating			80	79	87		
Moisture removal			L/h (pints/h)	1.0 (1.8)	1.3 (2.3)	1.8 (3.2)	2.1 (3.7)	
Maximum operating current*1		Cooling		A	6.5			
		Heating			9.0			
Fan	Airflow rate	Cooling	HIGH	m³/h	650	700	770	
			MED		540	560	600	
			LOW		430		450	
			QUIET		270		280	
		Heating	HIGH		720	750	770	800
			MED		580	610	640	660
			LOW		460	470	520	
			QUIET		330		340	
	Type × Qty	Crossflow fan × 1						
	Motor output		W	22	24	27	30	
Sound pressure level*2		Cooling	HIGH	dB (A)	38	40	43	
			MED		33	34	35	36
			LOW		29		30	
			QUIET		20		24	
		Heating	HIGH		41	42	44	
			MED		35	36	38	39
			LOW		31		33	
			QUIET		22		24	
Sound power level		Cooling	HIGH	dB (A)	54	55	57	
		Heating			56	57	58	59
Heat exchanger		Dimensions (H × W × D)		mm	Main 1: 210 × 670 × 26.6 Main 2: 112 × 670 × 20.0		Main 1: 210 × 670 × 26.6 Main 2: 112 × 670 × 20.0 Sub 1: 84 × 670 × 13.3	
		Fin pitch			Main 1: 1.2 Main 2: 1.1		Main 1: 1.2 Main 2: 1.1 Sub 1: 1.4	
		Rows × Stages		Main 1: 2 × 10 Main 2: 2 × 7		Main 1: 2 × 10 Main 2: 2 × 7 Sub 1: 1 × 4		
		Pipe type		Copper tube				
		Fin type		Aluminum				
Enclosure		Material		Polystyrene				
		Color		KETF: White + Pearl white (painted) Approximate color of Munsell N 9.25/ KETF-B: Dark Gray + Silver (painted) Approximate color of Munsell 0.5P 3.5/0.2				
Dimensions (H × W × D)		Net		mm	295 × 950 × 230			
		Gross			284 × 1,027 × 357			
Weight		Net		kg	11.0			11.5
		Gross			14.5			15.0
Connection pipe		Size	Liquid Gas	mm (in)	Ø6.35 (Ø1/4)			
		Method			Ø9.52 (Ø3/8) Flare			

Type			Wall mounted			
			Inverter, Heat pump			
Model name			ASEG07KETF ASEG07KETF-B	ASEG09KETF ASEG09KETF-B	ASEG12KETF ASEG12KETF-B	ASEG14KETF ASEG14KETF-B
Drain hose	Material		PP+HDPE			
	Tip diameter	mm	Ø13.8 (I.D.), Ø15 to Ø16.8 (O.D.)			
Operation range	Cooling	°C	18 to 32			
		%RH	80 or less			
	Heating	°C	16 to 30			
Remote controller			Wireless (Option: Wired, Mobile app ^{*3} [AIRSTAGE Mobile])			
NOTES:						
- Specifications are based on the following conditions: - Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB. - Heating: Indoor temperature of 20°CDB/15°CWB, and outdoor temperature of 7°CDB/6°CWB. - Pipe length: 5.0 m, Height difference: 0 m. (Between outdoor unit and indoor unit.) - Protective function might work when using it outside the operation range. *1: Maximum operating current is the total current of the indoor unit and the outdoor unit. *2: Sound pressure level: - Measured values in manufacturer's anechoic chamber. - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here. *3: Available on Google Play™ store or on App Store®. - This data is based on EN 14511 standard.						